

250w □□□□□□□□□□

□□□□UV□□□□UV□□□□□□□□□□ □□□□□□



□ □ □ □ □

電圧(V)	220V(±10%)
光束密度(lm/w)	125
光束径	1φ
照射面積	約100cm ²
光源	XHA





□□□□□

□□□□GE

□□ □□

□□□□□□□□□□



TYPE	Operating current	Operating voltage	Luminous Flux	Average Life time	Wind cooling speed	Electrode distance	NO.
型號	工作電流 (A)	工作電壓 (V)	光通量 (lm)	平均壽命 (h)	風冷速度 (M/sec)	極間距離 (mm)	圖號
XHA50	4	12.5	1300	400	5	0.6	2
XHA75	5	14	1400	500	5	1.5	2
XHA150	8.5	18	3200	800	5	2.6	3
XHA150/TC	8.5	18	3200	800	5	2.6	1
XHA250/TC	16	16	4800	800	5	2	1
XHA250	16	16	4800	800	5	2	3
XHA350/TC	16	22	11500	800	5	3	1
XHA350	16	22	11500	800	5	3	3
XHA450	25	18	13000	1000	5	2.7	5
XHA500	25	20	14200	1000	5	4	6
XHA500/H	28	17	14500	800	5	4	5
XHA750	33	23	24000	800	5	3.7	6

